## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

A method for providing custom probe arrays of biological 1. (Currently Amended) molecules, comprising the acts of:

receiving a first user selection from a first user of one or more probe set identifiers that identify a first set of probe sets each probe set comprising one or more potential probes, and an indication from the user to share a second selection from the first user to share available space on a custom probe array design with one or more additional users:

identifying a second set of one or more probe sets selected by the one or more additional users;

determining one or more verified probe sets of verified probes corresponding to at least one of the probe set identifiers;

generating the custom probe array design comprising the verified first and second sets of probe sets, wherein the first and second sets of probe sets together comprise a number of probe sets that is less than or equal to a total number of probe sets available for the custom probe array design;

providing a representation of the custom probe array design to the first user via one or more graphical user interfaces, wherein the one or more graphical user interfaces

are enabled to receive a user selection specifying acceptance, modification, or rejection of the custom probe array design; and

providing to the <u>first</u> user one or more probe arrays <u>based on produced using</u> the custom probe array design, and responsive to the user specification of acceptance or modification, wherein at least one of the probe detects nucleic acids.

- (Currently Amended) The method of claim 1, wherein:
- one or more of the probe arrays is enabled to diagnose capable of diagnosing a disease and/or medical condition.
- 3. (Cancelled)
- 4. (Currently Amended) The method of claim 1, wherein:
  the one or more probe arrays comprise probes are capable of hybridizing with biological molecules.
- 5. (Currently Amended) A method for providing custom probe arrays, comprising the acts of:

receiving a <u>first user</u>-selection <u>from a first user</u> of one or more probe set identifiers that identify a <u>first set of probe sets each probe set comprising</u> one or more <u>potential</u> probes, and <u>an indication from the user to share</u> a <u>second selection from the first user to share available space on a custom probe array design with one or more additional users;</u>

identifying a second set of one or more probe sets selected by the one or more additional users:

determining one or more verified probe sets of verified probes corresponding to at least one of the probe set identifiers;

generating the custom probe array design comprising the verified first and second sets of probe sets, wherein the first and second sets of probe sets together comprise a number of probe sets that is less than or equal to a total number of probe sets available for the custom probe array design;

providing a representation of the custom probe array design to the <u>first</u> user via one or more graphical user interfaces, wherein the one or more graphical user interfaces are enabled to receive <u>capable of receiving</u> a <u>third user</u> selection <u>from the first user</u> specifying acceptance, modification, or rejection of the custom probe array design; and

providing to the <u>first</u> user one or more probe arrays <u>based on the produced using</u>

the custom probe array design and responsive to the user specification of acceptance or modification.

- 6. (Currently Amended) The method of claim 5, wherein:
- the <u>first</u>, second, <u>and third</u> user selection is <u>selections</u> are received over the Internet.
- 7. (Original) The method of claim 5, wherein:

  the probe set identifiers comprise sequence information.

- 8. (Currently Amended) The method of claim 5, wherein:

  the probe set identifiers are selected by the <u>first</u> user from a predetermined list.
- 9. (Previously Presented) The method of claim 8, wherein: each item on the list corresponds to a gene.
- 10. (Cancelled)
- 11. (Previously Presented) The method of claim 5, wherein:

  the custom probe array design is generated using one or more probe array format factors.
- 12. (Currently Amended) The method of claim 11, wherein:

  some or all of the probe array format factors are provided by the <u>first</u> user and the act of receiving includes receiving user selected a fourth selection of the probe array format factors from the first user.
- 13. (Previously Presented) The method of claim 11, wherein:

  the probe array format factors include one or more indicators of geographic dispersion of probe sets on the probe array.
- 14. (Currently Amended) The method of claim 5[[13]], wherein:

the <u>one or more probe arrays comprise</u> substrate material includes one or more selected from the <u>proup consisting</u> of glass, silica, optical fibers, beads, resins, gels, or microspheres.

- 15. (Currently Amended) The method of claim 11[[13]], wherein:

  the act of generating further includes modifying or rejecting one or more usersclected probe array format factors.
- 16. (Original) The method of claim 5, further comprising the act of:
  the graphical user interface is provided over a network.
- 17. 18. (Cancelled)
- 19. (Currently Amended) A system for providing custom probe arrays, comprising:

  an input manager that receives a <u>first user</u> selection <u>from a first user</u> of one or

  more probe set identifiers that identify a <u>first set of probe sets each probe set comprising</u>

  one or more <u>potential</u> probes, and <u>an indication from the user to share</u> a <u>second selection</u>

  from the <u>first user to share available space on a custom probe array design with one or</u>

  more additional users;

a gene or EST verifier that determines one or more verified probe sets of verified probes corresponding to at least one of the probe-set identifiers;

a probe array generator that <u>identifies a second set of one or more probe sets</u>

<u>selected by the one or more additional users and generates the custom probe array design</u>

comprising the verified first and second sets of probe sets, wherein the first and second sets of probe sets together comprise a number of probe sets that is less than or equal to a total number of probe sets available for the custom probe array design; and

a user data processor that provides a representation of the custom probe array design to the first user via one or more graphical user interfaces, wherein the one or more graphical user interfaces are enabled to receive capable of receiving a user selection specifying acceptance, modification, or rejection of the custom probe array design, and one or more probe arrays are provided to the first user based on in response to a user sclection specifying acceptance or modification of the custom probe array design.

- The system of claim 19, wherein: 20. (Currently Amended) the first, second and third user selection is selections are received over the Internet.
- 21. (Original) The system of claim 19, wherein: the probe set identifiers comprise sequence information.
- The system of claim 19, wherein: 22. (Currently Amended) the probe set identifiers are selected by the first user from a predetermined list.
- The system of claim 22, wherein: 23. (Previously Presented) each item on the list corresponds to a gene.

24. (Cancelled)

25. (Previously Presented) The system of claim 19, wherein:

the probe array generator further generates the custom probe array design using one or more probe array format factors

26. (Currently Amended) The system of claim 25, wherein:

the input manager further receives some or all of the probe array format factors from the <u>first</u> user, including one or more user-selected probe array format factors.

27. (Previously Presented) The system of claim 25, wherein:

the one or more probe array format factors include one or more indicators of geographic dispersion of probe sets on the probe array.

28. (Currently Amended) The system of claim 27, wherein:

the <u>one or more probe arrays comprise</u> substrate material <del>includes one or more</del> selected from the group consisting of glass, silica, optical fibers, beads, resins, gels, or microspheres.

29. (Previously Presented) The system of claim 27, wherein:

the probe array generator further modifies or rejects the one or more user-selected probe array format factors.

30. (Original) The system of claim 19, wherein:

the graphical user interface is provided over a network.

31. - 32. (Cancelled)

33. (Currently Amended) A genomic portal system for providing custom probe arrays, comprising:

an application server comprising an input manager that receives a first user selection from a first user of one or more probe set identifiers that identify a first set of probe sets each probe comprising one or more potential probes and an indication from the user to share a second selection from the first user to share available space on a custom probe array design with one or more additional users, a gene or EST verifier that determines one or more verified probe sets of verified probes corresponding to at least one of the probe set identifiers, a probe array generator that identifies a second set of one or more probe sets selected by the one or more additional users and generates the custom probe array design comprising the verified first and second sets of probe sets, wherein the first and second sets of probe sets together comprise a number of probe sets that is less than or equal to a total number of probe sets available for the custom probe array design, and a user data processor that provides a representation to the first user of the custom probe array design via one or more graphical user interfaces, wherein the one or more graphical user interfaces are enabled to receive capable of receiving a user selection specifying acceptance, modification, or rejection of the custom probe array design, and

one or more probe arrays are provided to the <u>first user based on in response to a user</u> selection specifying acceptance or modification of the custom probe array design; and

a network server comprising an output manager that provides to the <u>first</u> user one or more probe arrays based on produced using the custom probe array design.

34. (Previously Presented) The system of claim 33, wherein:

the network server further comprises an input manager that receives the first selection user input; and

the system further comprises one or more user computers that enable a user to provide accepts the first user selection of one or more probe set identifiers from the first user and provides the first selection to the network server.

35. (Currently Amended) The system of claim 33, wherein:

the output manager identifies user data processor provides the one or more custom probe arrays array design to the first user via the internet.

36.-83. (Cancelled)

84. (Currently Amended) A method for providing custom probe arrays, comprising the acts of:

receiving a <u>first user</u> selection <u>from a first user</u> of one or more probe set identifiers that each identify a <u>first set of probe sets each probe set comprising plurality of potential one or more probes and <u>an indication from the user to share</u> a <u>second selection</u></u>

from the first user to share available space on a custom probe array design with one or more additional users:

identifying a second set of one or more probe sets selected by the one or more additional users:

determining verified probe sets of verified probes corresponding to at least one of the probe set identifiers;

generating the custom probe array design comprising the verified first and second sets of probe sets, wherein the first and second sets of probe sets together comprise a number of probe sets that is less than or equal to a total number of probe sets available for the custom probe array design; and

providing to the first user one or more probe arrays based on produced using the custom probe array design.